

Product selector

Параметри	Застосування	UNIFACE									PAVING			SOLID							
		GS	SS	ASSIST GS	ASSIST SS	MULTI GS	MULTI SS	AL	AL shallow	SMART AL	GS	ASSIST GS	MULTI GS	GS	SS	ASSIST GS	ASSIST SS	MULTI GS	MULTI SS	AL	
Розташування	Усередині приміщення	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Зовні будівель	✓	✓	✓	✓	✓	✓	✗	✗	✗	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗
Застосування	Аеропорти	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗	✗	✗	✓	✓	✓	✓	✓	✓	✓	✓
	Фармацевтика	✗	✓	✗	✓	✗	✓	✗	✗	✗	✗	✗	✗	✗	✓	✗	✓	✗	✓	✗	✗
	Побут	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗	✗	✗	✓	✓	✓	✓	✓	✓	✓	✓
	Виробництво їжі та напоїв	✗	✓	✗	✓	✗	✓	✗	✗	✗	✗	✗	✗	✗	✓	✗	✓	✗	✓	✗	✗
	Лікарні	✗	✓	✗	✓	✗	✓	✓	✓	✓	✗	✗	✗	✗	✓	✗	✓	✗	✓	✓	✓
	Промислові будівлі	✓	✓	✓	✓	✓	✓	✓	✗	✗	✗	✗	✗	✓	✓	✓	✓	✓	✓	✓	✓
	Благоустрій	✓	✓	✓	✓	✓	✓	✗	✗	✗	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗
	Пішохідні зони	✓	✓	✓	✓	✓	✓	✗	✗	✗	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗
	Тюрьми	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗	✗	✗	✓	✓	✓	✓	✓	✓	✓	✓
	Паркінги	✓	✓	✓	✓	✓	✓	✗	✗	✗	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗
	Залізничні станції	✓	✓	✓	✓	✓	✓	✗	✗	✗	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗
	Резиденції	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Школи	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗	✗	✗	✓	✓	✓	✓	✓	✓	✓	✓
	Спортивні споруди	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗	✗	✗	✓	✓	✓	✓	✓	✓	✓	✓
	Душові зони	✗	✓	✗	✓	✗	✓	✓	✓	✓	✓	✗	✗	✗	✗	✓	✗	✓	✗	✓	✓
	Клас навантаження	L15 / A15	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
M125 / B125		✓	✓	✓	✓	✓	✓	✓	✗	✗	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗
C250		✓	✓	✓	✓	✓	✗	✗	✗	✗	✓	✓	✓	✗	✗	✗	✗	✗	✗	✗	✗
Нормативні док-ти	EN 1253-4	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗
	EN 124	✗	✗	✗	✗	✗	✗	✗	✗	✗	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Інші параметри	Заповнення бетоном C35/45	✓	✓	✓	✓	✓	✓	✓	✓	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗
	Фінішне покриття до 15 мм	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗
	Заповнення люка до 80 мм	✗	✗	✗	✗	✗	✗	✗	✗	✗	✓	✓	✓	✗	✗	✗	✗	✗	✗	✗	✗
	Заповнення люка до 120 мм	✗	✗	✗	✗	✗	✗	✗	✗	✗	✓	✗	✓	✗	✗	✗	✗	✗	✗	✗	✗
	Відсутність вологи	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗	✓	✓	✓	✓	✓	✓	✓	✓
	Відсутність запахів	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗	✓	✓	✓	✓	✓	✓	✓	✓
	Пневматичний пристрій	✗	✗	✓	✓	✗	✗	✗	✗	✗	✗	✓	✗	✗	✗	✓	✓	✗	✗	✗	✗
	Укріплюючі балки	✗	✗	✗	✗	✓	✓	✗	✗	✗	✗	✗	✓	✗	✗	✗	✗	✓	✓	✓	✗

Рекомендації з підбору люків