



Qmax



Гідравлічні характеристики ACO Qmax®

ACO Qmax® 700

Поздовжній ухил поверхні	0%			0.5%			1%		
	Q (л/с)	q (л/с·м)	A (м²)	Q (л/с)	q (л/с·м)	A (м²)	Q (л/с)	q (л/с·м)	A (м²)
Довжина лінії, (м)									
50	250.0	5.00	18000	345.0	6.90	24840	405.0	8.10	29160
100	230.0	2.30	16560	370.0	3.70	26640	450.0	4.50	32400
200	200.0	1.00	14400	406.9	2.03	29300	520.0	2.60	37440
300	183.3	0.61	13200	438.9	1.46	31600	550.0	1.83	39600
400	170.8	0.43	12300	458.3	1.15	33000	559.7	1.40	40300
500	160.0	0.32	11520	468.1	0.94	33700	565.3	1.13	40700
600	148.5	0.25	10690	473.6	0.79	34100	570.8	0.95	41100
700	140.4	0.20	10110	477.8	0.69	34400	575.0	0.83	41400
800	136.0	0.17	9792	477.8	0.60	34400	577.8	0.72	41600
900	129.3	0.14	9310	477.8	0.53	34400	577.8	0.64	41600
1000	125.0	0.13	9000	477.8	0.48	34400	577.8	0.58	41600

