



Qmax



Гідравлічні характеристики АСО Qmax®

АСО Qmax® 900

Поздовжній ухил поверхні	0%			0.5%			1%		
	Q (л/с)	q (л/с-м)	A (м²)	Q (л/с)	q (л/с-м)	A (м²)	Q (л/с)	q (л/с-м)	A (м²)
Довжина лінії, (м)									
50	466.5	9.33	33588	620.0	12.40	44640	730.0	14.60	52560
100	440.0	4.40	31680	675.0	6.75	48600	835.0	8.35	60120
200	400.0	2.00	28800	748.0	3.74	53856	950.0	4.75	68400
300	370.5	1.24	26676	786.0	2.62	56592	1005.0	3.35	72360
400	343.2	0.86	24710	808.0	2.02	58176	1027.8	2.57	74000
500	322.5	0.65	23220	825.0	1.65	59400	1045.8	2.09	75300
600	309.0	0.52	22248	834.0	1.39	60048	1055.6	1.76	76000
700	296.8	0.42	21370	841.8	1.20	60606	1064.0	1.52	76608
800	284.0	0.36	20448	852.0	1.07	61344	1075.2	1.34	77414
900	274.5	0.31	19764	857.7	0.95	61754	1080.0	1.20	77760
1000	265.0	0.27	19080	863.0	0.86	62136	1086.0	1.09	78192

