
Square top

Product information for the product group



ACO Product benefits

- Fully inspectable and cleanable
- Fully removable and easily cleanable stainless steel foul air trap (FAT)
- Full drainability
- Internal radii equal or larger than 3 mm
- Fully welded hygienic joints
- Steel thickness min. 1,5 mm
- Edge infill
- ACO protective cover available
- Fully pickled and passivated
- ACO Building Drainage BIM Revit libraries
- Certified according to EN 1253-1
- Hygienic design following EN 1672, EN ISO 14159 and EHEDG document 8, 13 and 44
- Available in 1.4301 (304) or 1.4404 (316L) grades of stainless steel
- Adjustable EasyFix leveling feet
- Wide range of gratings for various load classes including slip resistant solutions
- Silt basket available as accessory

Item Technical Data 408014

Recess	Outlet diameter	Flow rate	Odour trap	Material			
[mm]	[mm]	[l/s]					
Extended edge							
200 x 200	75	2.6	With	1.4301			

Accessories

Description	Item number
Silt basket Stainless steel 0,3 litre capacity	
Material grade 1.4301 (304)	416906
Material grade 1.4404 (316L)	416907
ACO tundish Stainless steel Material grade 1.4301 (304)	413546



Item number: 408014 Version: 07.09.2020 Page 1 of 2 Item number: 408014

Description		
 Fixed height,vertical Telescopic, vertical Made from 1.4404 (316) grade of stainless steel NBR 		
ACO fire resistant kit for gully 157/DN 75	416932	
ACO fire resistant kit for gully 157/DN 110	416933	

You can find further accessories under → https://www.buildingdrainage.aco/suche/?q=408014



Item number: 408014 Version: 07.09.2020 Page 2 of 2