
## **Square top**

## Product information for the product group



# ACO Product benefits

- Fully inspectable and cleanable
- Fully removable and easily cleanable stainless steel foul air trap (FAT)
- Full drainability
- Internal radii equal or larger than 3 mm
- Fully welded hygienic joints
- Steel thickness min. 1,5 mm
- Edge infill
- ACO protective cover available
- Fully pickled and passivated
- ACO Building Drainage BIM Revit libraries
- Certified according to EN 1253-1
- Hygienic design following EN 1672, EN ISO 14159 and EHEDG document 8, 13 and 44
- Available in 1.4301 (304) or 1.4404 (316L) grades of stainless steel
- Adjustable EasyFix leveling feet
- Wide range of gratings for various load classes including slip resistant solutions
- Silt basket available as accessory

### **Item Technical Data 408015**

Recess	Outlet diameter	Flow rate	Odour trap	Material			
[mm]	[mm]	[l/s]					
Extended edge							
200 x 200	110	2.8	With	1.4301			

#### **Accessories**

Description	Item number
Silt basket  Stainless steel  0,3 litre capacity	
Material grade 1.4301 (3	04) <b>416906</b>
Material grade 1.4404 (31	6L) <b>416907</b>
ACO tundish  Stainless steel  Material grade 1.4301 (304)	413546



Item number: 408015 Version: 07.09.2020 Page 1 of 2

Description		
<ul> <li>Fixed height,vertical</li> <li>Telescopic, vertical</li> <li>Made from 1.4404 (316) grade of stainless steel</li> <li>NBR</li> </ul> ACO fire resistant kit for gully 157/DN 75	416932	
ACO fire resistant kit for gully 157/DN 110	416933	

You can find further accessories under → https://www.buildingdrainage.aco/suche/?q=408015



Item number: 408015 Version: 07.09.2020 Page 2 of 2